

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

UMEGUARD SX HARDENER

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paint and/or related product.

1.3. Details of the supplier of the safety data sheet

Chugoku Paints B.V., Sluisweg 12, 4794 SW Heijningen, Po Box 73, 4793 ZH Fijnaart, The Netherlands, Tel.+31-167-526100, E-mail: msdsregistration@cmpeurope.eu

1.4. Emergency telephone number

National Poisons Information Service: England & Wales / NHS dial 111, Scotland NHS 24, <http://www.npis.org>
N.Ireland, Contact your local GP or pharmacist during normal hours, www.gpoutofhours.hscni.net for GP services Out-of-Hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 H225	Highly flammable liquid and vapour.
Skin Irrit. 2 H315	Causes skin irritation.
Eye Dam. 1 H318	Causes serious eye damage.
Skin Sens. 1 H317	May cause an allergic skin reaction.
STOT SE 3 H335	May cause respiratory irritation.
STOT RE 2 H373	May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 2 H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements



GHS02



GHS05



GHS07

Hazard pictogram(s):



GHS08



GHS09

Signal word: Danger

Labelling according to Regulation (EC) No 1272/2008 [CLP]:

Hazard statement(s):

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Supplemental hazard information (EU): Not applicable.

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

Precautionary statement(s)

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe vapours/spray.

P280: Wear protective gloves, protective clothing, eye protection, face protection.

P273: Avoid release to the environment.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor.

P370+P378: In case of fire: Use alcohol resistant foam to extinguish.

P391: Collect spillage.

Storage & Disposal: -

Contains (EC 1272/2008 18.3(b)):

Reaction mass of Ethylbenzene and Xylene.

Fatty acids, C18-unsatd., dimers, polymeric reaction products with tall-oil fatty acids and triethylenetetramine.

N-Butanol.

Extended details regarding health and environment, see Section 11 & 12.














2.3. Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Substances presenting a health or environmental hazard within the meaning of Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List. (*) For full text of H-statements, see SECTION 16.

Substance name	Identification number	% [weight]	Hazard statement Code(s) (*) / Hazard Class and Category Codes	
Reaction Mass Of Ethylbenzene And Xylene.	EG-nr: 905-588-0	40-45 %	H226 - Flam. Liq. 3	H319 - Eye Irrit. 2
	CAS-nr: -		H304 - Asp. Tox. 1	H332 - Acute Tox. 4
	Index: -		H312 - Acute Tox. 4	H335 - STOT SE 3
	Reach#: 01-2119488216-32		H315 - Skin Irrit. 2	H373 - STOT RE 2
	  		SCL / M-factor / ATE: H312-ATE 1100mg/kg bw, H332-ATE 29mg/l	
Fatty Acids, C18-Unsatd., Dimers, Polymeric Reaction Products With Tall-Oil Fatty Acids And Triethylenetetramine.	EG-nr: 500-191-5	35-40 %	H318 - Eye Dam. 1	-
	CAS-nr: 68082-29-1		H315 - Skin Irrit. 2	-
	Index: -		H317-(1A) - Skin Sens. 1A	-
	Reach#: 01-2119972320-44		H411 - Aquatic Chronic 2	-
	  			
Isopropyl Alcohol.	EG-nr: 200-661-7	10-15 %	H225 - Flam. Liq. 2	-
	CAS-nr: 67-63-0		H319 - Eye Irrit. 2	-
	Index: 603-117-00-0		H336 - STOT SE 3	-
	Reach#: 01-2119457558-25		-	-
	 			
N-Butanol.	EG-nr: 200-751-6	3-8 %	H226 - Flam. Liq. 3	H318 - Eye Dam. 1
	CAS-nr: 71-36-3		H302 - Acute Tox. 4	H336 - STOT SE 3
	Index: 603-004-00-6		H335 - STOT SE 3	-
	Reach#: 01-2119484630-38		H315 - Skin Irrit. 2	-
	  		SCL / M-factor / ATE: H302-ATE 500	
Amines, Polyethylenepoly-, Triethylenetetramine Fraction.	EG-nr: 292-588-2	0,3-0,8 %	H302 - Acute Tox. 4	H412 - Aquatic Chronic 3
	CAS-nr: 90640-67-8		H312 - Acute Tox. 4	-
	Index: 612-059-00-5		H314-(1B) - Skin Corr. 1B	-
	Reach#: 01-2119487919-13		H317 - Skin Sens. 1	-
	 		SCL / M-factor / ATE: H302-ATE 500, H312-ATE 1100	

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

SECTION 4: First aid measures**4.1. Description of first aid measures**

Pay attention to your own safety! In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

following inhalation:

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

following skin contact:

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

following eye contact:

Remove contact lenses, if present and easy to do. Irrigate copiously with clean, fresh water, holding the eyelids apart for at least 15 minutes and seek immediate medical advice.

following ingestion:

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed**Potential acute symptoms and effects****following inhalation:**

Exposure to vapours may cause a health hazard. Serious effects may be delayed following exposure.

May cause respiratory irritation.

following skin contact:

Causes skin irritation.

following eye contact:

Causes serious eye damage.

following ingestion:

No known significant effects or critical hazards.

Potential delayed symptoms and effects**following inhalation:**

No specific data.

following skin contact:

May cause an allergic skin reaction.

following eye contact:

Adverse symptoms may include the following: irritation, watering, redness

following ingestion:

No specific data.

4.3. Indication of any immediate medical attention and special treatment needed**Notes to physician**

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

No specific treatment.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Recommended: alcohol resistant foam, CO2, powders, water spray/mist.

Extinguishing media which must not be used for safety reasons:

Water jet. Zincdust containing products should not be extinguished with water.

**5.2. Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. See Section 10.

5.3. Advice for firefighters

There is no one clothing material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Fire fighter's clothing conforming to European standard EN469 provides a basic level of protection for chemical incidents. Appropriate breathing apparatus may be required (Self-Contained Breathing Apparatus (SCBA)). Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel: Comply with company's emergency procedures. Exclude sources of ignition and ventilate the area. Use safety goggles or safety glasses, as well as any other appropriate personal protective equipment, at all times. Avoid breathing vapours. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Refer to protective measures listed in Sections 7 and 8.

For emergency responders: See Section 8 for information on appropriate personal protective equipment. See also the information: "For non-emergency personnel".

6.2. Environmental precautions

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Place in a suitable container. Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. No sparking tools should be used. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses. Isolate from sources of heat, sparks and open flame.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

Information regarding fire and explosion hazard

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

Notes on joint storage

Store away from oxidising agents, from strongly alkaline and strongly acid materials.



Additional information on storage conditions

Observe label precautions. Store between 0°C and 40°C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

Application: Airless spray, Brush, Roller (See also Technical Data Sheet.)

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Limits for occupational exposure and / or biological limit values		
	LIMIT VALUES TWA8h - STEL15 ppm-mg/m ³	LIMIT VALUES TWA8h - STEL15 ppm-mg/m ³
Reaction Mass Of Ethylbenzene And Xylene.	TWA8h - ppm / - mg/m ³	TWA8h - ppm / - mg/m ³
	STEL - ppm / - mg/m ³	STEL15 - ppm / - mg/m ³
	Annotations -	Notation -
Fatty Acids, C18-Unsatd., Dimers, Polymeric Reaction Products With Tall-Oil Fatty Acids And Triethylenetetramine.	TWA8h - ppm / - mg/m ³	TWA8h - ppm / - mg/m ³
	STEL - ppm / - mg/m ³	STEL15 - ppm / - mg/m ³
	Annotations -	Notation -
Isopropyl Alcohol.	TWA8h 400 ppm / 999 mg/m ³	TWA8h - ppm / - mg/m ³
	STEL 500 ppm / 1250 mg/m ³	STEL15 - ppm / - mg/m ³
	Annotations -	Notation -
N-Butanol.	TWA8h - ppm / - mg/m ³	TWA8h - ppm / - mg/m ³
	STEL 50 ppm / 154 mg/m ³	STEL15 - ppm / - mg/m ³
	Annotations Sk	Notation -
Amines, Polyethylenepoly-, Triethylenetetramine Fraction.	TWA8h - ppm / - mg/m ³	TWA8h - ppm / - mg/m ³
	STEL - ppm / - mg/m ³	STEL15 - ppm / - mg/m ³
	Annotations -	Notation -

U.K. - TWA=Time Weighted Average (8hr) - STEL=Short-term exposure limit (15-minute reference period) - H.S.E. Health and Safety Commission.

Europe - TWA = Time Weight Average (8hr) - Measured or calculated in relation to a reference period of 8 hours time-weighted average (TWA) - STEL = Short-term exposure limit - A limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified - SCOEL

Annotations / Notations:

BMGVs: Biological monitoring guidance values.

Carc: Capable of causing cancer and/or heritable genetic damage.

Inh.: Inhalable fraction.

Resp.: Respirable fraction.

Sen: Capable of causing occupational asthma.

Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

Skin: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin.

DNEL

DNEL - Not available.

PNEC

PNEC - Not available.

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Personal Protection

Respiratory protection



If workers could be exposed to concentrations above the exposure limit they should use a respirator to EN 140, fitted with a filter suitable for both particulates and vapours to EN14387, with an assigned protection factor of at least 10 (e.g. A2P3).

Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Hand protection



There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. At repeated or prolonged contact; use gloves tested according to EN 374. Viton-gloves offer good protection for intense contact with most solvents, e.g. complete immersion in solvent.

Nitrile gloves offer good protection during spray application. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. The breakthrough time must be greater than the end use time of the product. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. USE PE gloves as under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.

Gloves for repeated or prolonged exposure (Permeation breakthrough times > 480 min) - High Protection:		
Material:	Minimum Thickness:	Chemical resistance:
Polyethylene (PE) Gloves	0,062mm	High
Butyl Viton Gloves	0,70mm	High
Gloves for repeated or prolonged exposure (Permeation breakthrough times 240 - 480 min) - High Protection:		
Material:	Minimum Thickness:	Chemical resistance:
Polyethylene (PE) Gloves	0,062mm	High
Butyl Viton Gloves	0,70mm	High
Gloves for repeated or prolonged exposure (Permeation breakthrough times 120-240 min) - Medium Protection:		
Material:	Minimum Thickness:	Chemical resistance:
Polyethylene (PE) Gloves	0,062mm	High
Butyl Viton Gloves	0,70mm	High
Gloves for repeated or prolonged exposure (Permeation breakthrough times 60 - 120 min) - Medium Protection:		
Material:	Minimum Thickness:	Chemical resistance:
Polyethylene (PE) Gloves	0,062mm	High
PVA Gloves	0,2-0,3mm	High
Butyl Viton Gloves	0,70mm	High

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

Gloves for short term exposure / splash protection (Permeation breakthrough times 30 - 60 min):		
Material:	Minimum Thickness:	Chemical resistance:
Polyethylene (PE) Gloves	0,062mm	High
PVA Gloves	0,2-0,3mm	High
Butyl Viton Gloves	0,70mm	High
Nitrile Gloves	0,31mm	High
Gloves for short term exposure / splash protection (Permeation breakthrough times 10 - 30 min):		
Material:	Minimum Thickness:	Chemical resistance:
Polyethylene (PE) Gloves	0,062mm	High
PVA Gloves	0,2-0,3mm	High
Butyl Viton Gloves	0,70mm	High
Butyl Gloves	0,3mm	High
Neoprene Gloves	<0,4mm	High
Nitrile Gloves	0,175mm	High
Non suitable Gloves - non exhaustive list (Permeation breakthrough times < 10 min):		
Material:	Thickness (or less):	
Natural Rubber Gloves	0,75mm	
Nitrile Gloves	-	
Neoprene Gloves	0,75mm	

**Eye/face protection**

Use safety eyewear tested according to EN 166 designed to protect against splash of liquids.

**Skin protection**

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

**Environmental exposure controls**

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****(a) Physical state**

Liquid

(b) Colour

Colourless.

(c) Odour

Amine-like odour.

(d) Melting point/freezing point

Not applicable due to nature of the product.

(e) Boiling point or initial boiling point and boiling range

Not applicable due to nature of the product. Lowest Boiling Point: Isopropyl Alcohol. - 82°C

(f) Flammability

Vapours are ignitable. See Flash point (h).

(g) Lower and upper explosion limit

The product itself is not explosive, but the formation of an explosive mixture of vapour or dust with air is possible.

Reaction Mass Of Ethylbenzene And Xylene.	1.0-7.0%
Fatty Acids, C18-Unsatd., Dimers, Polymeric Reaction Products With Tall-Oil Fatty Acids And Triethylenetetramine.	Not applicable.
Isopropyl Alcohol.	2-12%
N-Butanol.	1.4-11.3%

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

(g) Lower and upper explosion limit

Amines, Polyethylenepoly-, Triethylenetetramine Fraction.

0.7-7.2%

(h) Flash point

17°C - Method: ASTM D3278-96 (Re-appr.2004)

(i) Auto-ignition temperature

Not applicable due to nature of the product.

Lowest auto ignition temperature: Amines, polyethylenepoly-, triethylenetetramine fraction. - 325°C

(j) Decomposition temperature

Not applicable due to nature of the product.

(k) pH

Not applicable due to nature of the product. Mixture is non-soluble (in water).

(l) Kinematic viscosity86 mm²/s @40°C - Method: ISO3219

Non-Newtonian liquid - thixotropic behaviour.

(m) Solubility

Not Soluble (in water).

(n) Partition coefficient n-octanol/water (log value)

Not applicable due to nature of the product.

(o) Vapour pressure

Reaction Mass Of Ethylbenzene And Xylene.

8.21 mbar

Fatty Acids, C18-Unsatd., Dimers, Polymeric Reaction Products With Tall-Oil Fatty Acids And Triethylenetetramine.

<0.1hPa

Isopropyl Alcohol.

42 mbar

N-Butanol.

5,6 mbar

Amines, Polyethylenepoly-, Triethylenetetramine Fraction.

<< 0.1 mbar

(p) Density and/or relative density

Relative density 0,91 @ 20°C - Method: ASTM D1475-98

(q) Relative vapour density

1-2 @ 20°C - Method: Calculated.

(r) Particle characteristics

Not applicable due to nature of the product.

9.2. Other information

Information with regard to physical hazard classes

No relevant information.

Other safety characteristics

No relevant information.

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

SECTION 10: Stability and reactivity**10.1. Reactivity**

No specific test data related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see Section 7).

10.3. Possibility of hazardous reactions

In combination with oxidizing agents, strongly alkaline and strongly acid materials, exothermic reactions and/or explosive reactions may occur or toxic vapours may arise.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials.

10.6. Hazardous decomposition products

Carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Substance name

Reaction Mass Of Ethylbenzene And Xylene. - LD50 Oral - >2000 mg/kg, Rat - LD50 Dermal - >2000 mg/kg, Rat - LC50 Inhalation - 29 mg/lRat,4h

Fatty Acids, C18-Unsatd., Dimers, Polymeric Reaction Products With Tall-Oil Fatty Acids And Triethylenetetramine. - LD50 Oral - >2000 mg/kg, Rat - LD50 Dermal - >2000 mg/kg, Rat - LC50 Inhalation - Not available.

Isopropyl Alcohol. - LD50 Oral - >5000 mg/kg, Rat - LD50 Dermal - >5000 mg/kg, Rabbit - LC50 Inhalation - >20 mg/lRat,4h

N-Butanol. - LD50 Oral - >2000 mg/kg, Rat - LD50 Dermal - >2000 mg/kg, Rabbit - LC50 Inhalation - >17,76 mg/lRat,4h

Amines, Polyethylenepoly-, Triethylenetetramine Fraction. - LD50 Oral - >2000 mg/kg, Rat - LD50 Dermal - 550 mg/kg, Rat - LC50 Inhalation - Not available.

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

Conclusion/Summary on mixture**Acute toxicity:**

ATEmix (oral) : No specific data.
ATEmix (Dermal) : No specific data.
ATEmix (Inhalation) : No specific data.

Skin corrosion/irritation:

Conclusion/Summary on mixture: Causes skin irritation.

Method: Additivity approach, No testdata available.

Serious eye damage/irritation:

Conclusion/Summary on mixture: Causes serious eye damage.

Method: Additivity approach, no testdata available.

Respiratory or skin sensitisation:

Conclusion/Summary on mixture

Respiratory sensitization Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

Skin sensitization May cause an allergic skin reaction. Method: Concentration Limit, no testdata available.

Germ cell mutagenicity:

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

Carcinogenicity:

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

Reproductive toxicity:

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

STOT - single exposure:

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

STOT - repeated exposure:

Conclusion/Summary on mixture: May cause damage to organs through prolonged or repeated exposure. Method: Concentration Limit, no testdata available.

Aspiration hazard:

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met.

Justification: Additivity approach / Kinematic viscosity: 86 mm²/s @40°C - Measured

Information on likely routes of exposure

Inhalation: Exposure to vapours may cause a health hazard. Serious effects may be delayed following exposure.

Ingestion: No specific data.

Skin exposure: Causes skin irritation. May cause an allergic skin reaction.

Eye exposure: Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: Adverse symptoms may include the following: Cough

Ingestion: No specific data.

Skin exposure: Adverse symptoms may include the following: irritation, redness.

Eye exposure: Adverse symptoms may include the following: irritation, watering, redness.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Short term exposure:**

Potential immediate effects: No specific data.

Potential delayed effects: No specific data.

Long term exposure:

Potential immediate effects: No specific data.

Potential delayed effects: No specific data.

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

Potential chronic health effects:**Conclusion/Summary on mixture**

General:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity:	No known significant effects or critical hazards.
Mutagenicity:	No known significant effects or critical hazards.
Teratogenicity:	No known significant effects or critical hazards.
Developmental effects:	No known significant effects or critical hazards.
Fertility effects:	No known significant effects or critical hazards.
Other information:	No relevant information.

Contains Fatty Acids, C18-Unsatd., Dimers, Polymeric Reaction Products With Tall-Oil Fatty Acids And Triethylenetetramine., Amines, Polyethylenepoly-, Triethylenetetramine Fraction. May produce an allergic reaction.

11.2 Information on other hazards**Endocrine disrupting properties**

No relevant information.

Other information

No relevant information.

SECTION 12: Ecological information

There are no data available on the mixture itself. Do not allow to enter drains or water courses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and classified for eco-toxicological hazards accordingly.

12.1. Toxicity**Substance name - Species - Exposure - Results**

Reaction Mass Of Ethylbenzene And Xylene. Acute (short-term) toxicity: Fish: LC50/96h - 2.6 mg/l, Crustacea: EC50/48h 1-10 mg/l (Daphnia magna), Algae/aquatic plants: EC50/72h 2.2 mg/L (Pseudokirchneriella subcapitata), Other organisms: Not available. Chronic (long-term) toxicity: Fish: NOEC >1.3 mg/L (Salmo gairdneri), Crustacea: NOEC 0.96mg/L, Algae/aquatic plants: NOEC 0.44mg/L, Other organisms: Not available.

Fatty Acids, C18-Unsatd., Dimers, Polymeric Reaction Products With Tall-Oil Fatty Acids And Triethylenetetramine. Acute (short-term) toxicity: Fish: LC50/96h 7,07mg/l (Danio rerio), Crustacea: EC50/48h 7,07mg/l (Daphnia magna), Algae/aquatic plants: EC50/72h 4,34 mg/L (Pseudokirchneriella subcapitata), Other organisms: Not available. Chronic (long-term) toxicity: Fish: LC10 5mg/l, Crustacea: Not available., Algae/aquatic plants: NOEC 0,5 mg/L, Other organisms: Not available.

Isopropyl Alcohol. Acute (short-term) toxicity: Fish: LC50/96h 9640 MG/l (Pimephales promelas), Crustacea: L50/24h 10000 mg/l (Daphnia magna), Algae/aquatic plants: >1000 mg/l, Other organisms: IC50/3D 2104 mg/kg soil dw (Lactuca sativa) Chronic (long-term) toxicity: Fish: Not available., Crustacea: Not available., Algae/aquatic plants: NOEC 1800 mg/L (Scenedesmus quadricauda), Other organisms: Not available.

N-Butanol. Acute (short-term) toxicity: Fish: LC50/96h 1376 mg/l (Pimephales promelas), Crustacea: EC50/48h 1328 mg/l (Daphnia magna), Algae/aquatic plants: EC50/96h 225 mg/l (Selenastrum capricornutum), Other organisms: Not available. Chronic (long-term) toxicity: Fish: Not available., Crustacea: NOEC 4,1 mg/l, Algae/aquatic plants: NOEC 129 mg/L, Other organisms: Not available.

Amines, Polyethylenepoly-, Triethylenetetramine Fraction. Acute (short-term) toxicity: Fish: LC50/96h 330mg/l (Pimephales promelas), Crustacea: EC50/48h 31,1mg/l (Daphnia magna), Algae/aquatic plants: EC50/72h 20mg/l (Selenastrum capricornutum), Other organisms: Not available. Chronic (long-term) toxicity: Fish: Not available., Crustacea: EC10 1.9 mg/L, Algae/aquatic plants: NOEC 1.34 mg/L, Other organisms: NOEC 62.5 mg/kg soil dw (Eisenia fetida)

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

12.2. Persistence and degradability**Substance name**

Reaction Mass Of Ethylbenzene And Xylene. - Readily biodegradable.

Fatty Acids, C18-Unsatd., Dimers, Polymeric Reaction Products With Tall-Oil Fatty Acids And Triethylenetetramine. - Readily biodegradable.

Isopropyl Alcohol. - Readily biodegradable.

N-Butanol. - Readily biodegradable.

Amines, Polyethylenepoly-, Triethylenetetramine Fraction. - Not readily biodegradable.

12.3. Bioaccumulative potential**Substance name****log Kow****BCF**

Reaction Mass Of Ethylbenzene And Xylene.

3,1

25,9

Fatty Acids, C18-Unsatd., Dimers, Polymeric Reaction Products With Tall-Oil Fatty Acids And Triethylenetetramine.

10,34

77.4 L/kg ww

Isopropyl Alcohol.

0,05

Not available.

N-Butanol.

0,88

3,16

Amines, Polyethylenepoly-, Triethylenetetramine Fraction.

-1,7

Not available.

12.4. Mobility in soil

Soil/water partition coefficient (KOC)

: Not available.

Mobility

: No relevant information.

12.5. Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6. Endocrine disrupting properties

No relevant information.

12.7. Other adverse effects

No relevant information.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**






Product / Packaging disposal: Dispose of containers contaminated by the product in accordance with local or national legal provisions. The European Waste Catalogue (2000/532/EC) classification of this product. Waste codes / waste designations according to LoW: 08 01 11* Waste paint and varnish containing organic solvents or other hazardous substances. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Waste should not be disposed of by release to sewers. Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers.

Containers which are not properly cleaned may contain (highly) flammable or explosive vapours.

Special precautions: Use appropriate protective equipment for the removal and / or disposal of this product.

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

SECTION 14: Transport information

	ADR / RID / ADN	IMDG-Code	IATA
14.1. UN number or ID number	UN 1263	UN 1263	UN 1263
14.2. UN			
	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label(s)			
14.4. Packing group	II	II	II
14.5. Environmental hazards	Yes Environmental hazardous substances (aquatic environment) 	Yes Marine Pollutant: Yes  Marine Pollutant substance(s): Fatty Acids, C18-Unsatd., Dimers, Polymeric Reaction Products With Tall-Oil Fatty Acids And Triethylenetetramine.	No
Additional information	Hazard Identification Number No.: 33	Emergency Schedule Number (EmS): F-E, S-E	

14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

The information in this Safety Data Sheet is required pursuant to

Annex II to regulation (EC) No 1907/2006 and its amendments.

The provisions of the Health and Safety at Work etc. Act [and the Control of Substances Hazardous to Health Regulations] apply to the use of this product at work.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

Seveso category (DIRECTIVE 2012/18/EU): P5c - E2 This product may add to the calculation for determining whether a site is within scope of the Seveso Directive on major accident hazards.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information**Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008****[CLP]:**

H225	Measured
H315	Additivity approach
H318	Additivity approach
H317	Concentration limit
H335	Additivity approach
H373	Concentration limit
H411	Summation method

Abbreviations and acronyms:

ADN	: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	: Acute Toxicity Estimate
BCF	: Bioconcentration factor
CLP	: Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	: Derived No Effect Level
IATA	: International Air Transport Association
IMDG-Code	: International Maritime Dangerous Goods
Kow	: octanol-water partition coefficient
LC50	: Lethal Concentration to 50 % of a test population
LD50	: Lethal Dose to 50% of a test population (Median Lethal Dose)
PBT	: Persistent, Bioaccumulative and Toxic substance
PNEC	: Predicted No Effect Concentration(s)
RID	: Regulations concerning the International Carriage of Dangerous Goods by Rail
STOT	: Specific Target Organ Toxicity
vPvB	: Very Persistent and Very Bioaccumulative

Product code: 426EE0000 - Version 6 - Revision Date: 13-07-2023

Full text of Hazard Statements appearing in Section 3.2.:

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314-(1B) Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H317-(1A) May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

Amendments: 13-07-2023, §2,3,8,9,11,12,14&16

The information of this SDS is based on the present state of our knowledge and on current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

UMEGUARD SX HARDENER

Safe Use of Mixtures Information for end-users (SUMI)

Title: Professional spray painting, near-industrial setting - CEPE_PW_01

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered




Indoor spray painting by professionals with efficient ventilation such as spray booth or local exhaust ventilation.

This safe use information is linked to: SWED CEPE_PW_01

Operational Conditions

Indoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year *

Risk Management Measures			
Contributing activity	Ventilation		Ventilation - air changes/hr
Preparation of material for application	Enhanced (mechanical) room ventilation		5-10
Loading of application equipment and handling of coated parts before curing	Enhanced (mechanical) room ventilation		5-10
Application	Local exhaust ventilation, spray booth or equivalent		Refer to relevant technical standards
Drying/curing	Enhanced (mechanical) room ventilation		5-10
Application equipment cleaning	Enhanced (mechanical) room ventilation		5-10
Waste management	Enhanced (mechanical) room ventilation		5-10
Contributing activity	Respiratory 	Eye 	Hands 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Drying/curing	None	None	None
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

UMEGUARD SX HARDENER

Safe Use of Mixtures Information for end-users (SUMI)

Title: Professional non-spray painting, near-industrial setting - CEPE_PW_02

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered




Indoor painting by professionals with brush, roller, putty knife etc. with enhanced ventilation or local exhaust ventilation

This safe use information is linked to: SWED CEPE_PW_02

Operational Conditions

Indoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year *

Risk Management Measures			
Contributing activity	Ventilation		Ventilation - air changes/hr
Preparation of material for application	Enhanced (mechanical) room ventilation		5-10
Loading of application equipment and handling of coated parts before curing	Enhanced (mechanical) room ventilation		5-10
Application	Local exhaust ventilation		Refer to relevant technical standards
Drying/curing	Enhanced (mechanical) room ventilation		5-10
Application equipment cleaning	Enhanced (mechanical) room ventilation		5-10
Waste management	Enhanced (mechanical) room ventilation		5-10
Contributing activity	Respiratory 	Eye 	Hands 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Drying/curing	None	None	None
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

UMEGUARD SX HARDENER

Safe Use of Mixtures Information for end-users (SUMI)

Title: Professional spray painting, indoor (without respiratory protection) - CEPE_PW_03a

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered



Indoor spray painting by professionals for general applications (e.g. decorative), with general room ventilation only (open doors/windows).

This safe use information is linked to: SWED CEPE_PW_03a

Operational Conditions

Indoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year *

Risk Management Measures			
Contributing activity	Ventilation		Ventilation - air changes/hr
Preparation of material for application	Good general room ventilation (e.g. open windows)		3-5
Loading of application equipment and handling of coated parts before curing	Good general room ventilation (e.g. open windows)		3-5
Application	Good general room ventilation (e.g. open windows)		3-5
Drying/curing	Good general room ventilation (e.g. open windows)		3-5
Application equipment cleaning	Good general room ventilation (e.g. open windows)		3-5
Waste management	Good general room ventilation (e.g. open windows)		3-5
Contributing activity	Respiratory	Eye 	Hands 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Drying/curing	None	None	None
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

*Preparation of material for application, Max.1-4h/day. *Loading / handling, Max.1-4h/day. *Application, Max.<15 min./day. *Application equipment cleaning, M:

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

UMEGUARD SX HARDENER

Safe Use of Mixtures Information for end-users (SUMI)

Title: Professional spray painting, indoor (with respiratory protection) - CEPE_PW_03b

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered




Indoor spray painting by professionals for specialist applications, with general room ventilation plus respiratory protection.

This safe use information is linked to: SWED CEPE_PW_03b

Operational Conditions

Indoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year *

Risk Management Measures			
Contributing activity	Ventilation		Ventilation - air changes/hr
Preparation of material for application	Good general room ventilation (e.g. open windows)		3-5
Loading of application equipment and handling of coated parts before curing	Good general room ventilation (e.g. open windows)		3-5
Application	Good general room ventilation (e.g. open windows)		3-5
Drying/curing	Good general room ventilation (e.g. open windows)		3-5
Application equipment cleaning	Good general room ventilation (e.g. open windows)		3-5
Waste management	Good general room ventilation (e.g. open windows)		3-5
Contributing activity	Respiratory 	Eye 	Hands 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Drying/curing	None	None	None
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

*Preparation of material for application, Max.1-4h/day. *Loading / handling, Max.1-4h/day. *Application equipment cleaning, Max.1-4h/day. *Waste Management

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

UMEGUARD SX HARDENER

Safe Use of Mixtures Information for end-users (SUMI)

Title: Professional painting, indoor brush/roller - CEPE_PW_04

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered



Indoor painting by professionals with brush or roller, with general room ventilation (open doors/windows).

This safe use information is linked to: SWED CEPE_PW_04

Operational Conditions

Indoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year *

Risk Management Measures			
Contributing activity	Ventilation		Ventilation - air changes/hr
Preparation of material for application	Good general room ventilation (e.g. open windows)		3-5
Loading of application equipment and handling of coated parts before curing	Good general room ventilation (e.g. open windows)		3-5
Application	Good general room ventilation (e.g. open windows)		3-5
Drying/curing	Good general room ventilation (e.g. open windows)		3-5
Application equipment cleaning	Good general room ventilation (e.g. open windows)		3-5
Waste management	Good general room ventilation (e.g. open windows)		3-5
Contributing activity	Respiratory	Eye 	Hands 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Drying/curing	None	None	None
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

*Preparation of material for application, Max.1-4h/day. *Loading / handling, Max.1-4h/day. *Application, Max.1-4h/day. *Application equipment cleaning, Max.1-

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

UMEGUARD SX HARDENER

Safe Use of Mixtures Information for end-users (SUMI)

Title: Professional spray painting, outdoor (without respiratory protection) - CEPE_PW_05a

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered



Outdoor spray painting by professionals for general applications (e.g. decorative).

This safe use information is linked to: SWED CEPE_PW_05a

Operational Conditions

Outdoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year *

Risk Management Measures			
Contributing activity	Ventilation		Ventilation - air changes/hr
Preparation of material for application	Outdoors		3-5
Loading of application equipment and handling of coated parts before curing	Outdoors		3-5
Application	Outdoors		3-5
Drying/curing	Outdoors		3-5
Application equipment cleaning	Outdoors		3-5
Waste management	Outdoors		3-5
Contributing activity	Respiratory	Eye 	Hands 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Drying/curing	None	None	None
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

*Preparation of material for application, Max.1-4h/day. *Loading / handling, Max.1-4h/day. *Application, Max.<15 min./day. *Application equipment cleaning, M:

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

UMEGUARD SX HARDENER

Safe Use of Mixtures Information for end-users (SUMI)

Title: Professional spray painting, outdoor (with respiratory protection) - CEPE_PW_05b

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered




Outdoor spray painting by professionals for specialist applications, with respiratory protection.

This safe use information is linked to: SWED CEPE_PW_05b

Operational Conditions

Outdoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year *

Risk Management Measures			
Contributing activity	Ventilation		Ventilation - air changes/hr
Preparation of material for application	Outdoors		3-5
Loading of application equipment and handling of coated parts before curing	Outdoors		3-5
Application	Outdoors		3-5
Drying/curing	Outdoors		3-5
Application equipment cleaning	Outdoors		3-5
Waste management	Outdoors		3-5
Contributing activity	Respiratory 	Eye 	Hands 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Drying/curing	None	None	None
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

*Preparation of material for application, Max.1-4h/day. *Loading / handling, Max.1-4h/day. *Application equipment cleaning, Max.1-4h/day. *Waste Management

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

UMEGUARD SX HARDENER

Safe Use of Mixtures Information for end-users (SUMI)

Title: Professional painting, outdoor brush/roller - CEPE_PW_06

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered



Outdoor painting by professionals with brush or roller.

This safe use information is linked to: SWED CEPE_PW_06

Operational Conditions

Outdoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year *

Risk Management Measures			
Contributing activity	Ventilation		Ventilation - air changes/hr
Preparation of material for application	Outdoors		3-5
Loading of application equipment and handling of coated parts before curing	Outdoors		3-5
Application	Outdoors		3-5
Drying/curing	Outdoors		3-5
Application equipment cleaning	Outdoors		3-5
Waste management	Outdoors		3-5
Contributing activity	Respiratory	Eye 	Hands 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Drying/curing	None	None	None
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

*Preparation of material for application, Max.1-4h/day. *Loading / handling, Max.1-4h/day. *Application, Max.1-4h/day. *Application equipment cleaning, Max.1-

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.